

SOLAR COATING SYSTEMS



SCS CLEARSEAL/PRIMER

SCS Clear Sealer/Primer stabilizes and secures substrates for the application of elastomeric coatings. It has the optimum balance of absorption into, and surface coating of, the substrate. Along with extremely high adhesion properties, this provides a bond far greater than typical coatings. Material has over 1500% elongation and can fill and/or bridge hairline cracks. Even when completely cured the surface remains tacky providing an optimum surface for the adhesion of elastomeric roof coatings.

FEATURES:

- **Rohm & Haas - 100% Acrylic Technology.**
- **High Elongation – Fills or bridges hairline cracks.**
- **Adhesion - Excellent adhesion to most non-ferrous substrates.**
- **Easy Application - Single component, spraying will give the best uniformity. It can also be brushed or rolled.**
- **Quick Surface Dry - Material will be dry to touch in approximately 30 minutes, and can be recoated in one hour.**
- **Environmentally Friendly - Water based; Asbestos, lead, and mercury free.**

TYPICAL PHYSICAL PROPERTIES: at 75°F

- | | |
|---------------------------|----------------------------------|
| • Color | White liquid, dries clear |
| • Solids by Weight | 42 ± 2% |
| • Solids by Volume | 40 ± 2% |
| • Tensile | 400 psi |
| • Elongation | 1600% |
| • Weight | 8.49 lb./Gal. |
| • Application Rate | 1/3 gal per square. |

LIMITATIONS AND PRECAUTIONS:

Do not apply when ambient temperature is below 50°F. Cold temperatures and high humidity will retard drying.

Store in tightly closed containers and protect from freezing.

Surface must be clean, dry, and free of rust and loose dirt.

Disclaimer: Our data is based on information from laboratory tests which are believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Solar Coating Systems control. We do not assume liability or responsibility of the product relative to coverage, performance, or injury resulting from its use. Liability, if any, is limited to replacement of product.

California Prop 65: Chemical Warning:

(California Health and Safety Code #25249.5 ET SEQ) Detectable amounts of some chemicals known to the state of CA to cause cancer, birth defects or other reproductive harm may be found in Solar Coating Systems petroleum based products and their vapors. Read and follow label directions and information on MSDS sheets and use care when handling or using petroleum products.