

SOLAR COATING SYSTEMS



SCS CRACK PATCH

SCS CRACK PATCH is a premixed, ready to use 100% acrylic polymer crack filler. It requires no additional cement or water. It is designed to repair cracks and holes in concrete walls up to 1/2" in width. Polyester can be used as reinforcement. It is highly flexible, trowels easily, and will not effloresce.

<p>Can be used on: Concrete</p> <p>PREPARATION: All surfaces must be dry and free of dust, dirt, oil, loose peeling paint and other foreign matter. Washing roof surface is recommended for best results. Surfaces with mildew or stains must be cleaned with bleach solution (2 parts water to 1 part bleach) prior to application of the product. Be certain all surfaces are thoroughly rinsed and dry prior to application.</p> <p>APPLICATION: Surface and air temperatures must be a minimum of 55° F and rising. Do not apply if rain or heavy dew is expected within 24 hours. Apply with trowel or stiff bristle brush. Allow to cure 24-48 hours prior to coating. Do not thin. Do not allow product to freeze before full cure.</p> <p>California Prop 65: Chemical Warning: (California Health and Safety Code #25249.5 ET SEQ) Detectable amounts of some chemicals known to the state of CA to cause cancer, birth defects or other reproductive harm may be found in Solar Coating Systems petroleum based products and their vapors. Read and follow label directions and information on MSDS sheets and use care when handling or using petroleum products</p> <p>Disclaimer: Our data is based on information from laboratory tests which are believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Solar Coating Systems control. We do not assume liability or responsibility of the product relative to coverage, performance, or injury resulting from its use. Liability, if any, is limited to replacement of product.</p>	<p>TYPICAL PHYSICAL CHARACTERISTICS</p> <table> <tr> <td>Weight per gallon</td> <td>14.00 lbs.</td> </tr> <tr> <td>Color :</td> <td>White</td> </tr> <tr> <td>Solids by Weight</td> <td>80.0%</td> </tr> <tr> <td>Solids by volume</td> <td>57%</td> </tr> <tr> <td>Flammability</td> <td>N/A (water based)</td> </tr> <tr> <td>Application temperature</td> <td>55° F and rising</td> </tr> <tr> <td>Consistency</td> <td>trowel</td> </tr> <tr> <td>Clean up with warm water and soap</td> <td></td> </tr> <tr> <td>Shelf life 1 year</td> <td></td> </tr> </table> <p>CAUTION! Harmful if swallowed, may cause eye, skin or respiratory irritation. Use with adequate ventilation. Keep out of reach of children</p> <p>FIRST AID: Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC23C or equivalent. In case of Ingestion – Contact a physician immediately. Eye Contact – Flush with of warm water and call a physician immediately. Skin contact – Wash thoroughly with soap and water.</p> <p>Regulatory/Environmental Characteristics:</p> <table> <tr> <td>Volatile Organic Content</td> <td>0.16 lb/gallon</td> </tr> <tr> <td>HMIS Rating</td> <td>H-1,F-0,R-0, PP-A</td> </tr> <tr> <td>RCRA Hazardous Substances</td> <td>none</td> </tr> <tr> <td>SARA Title 111 listing:</td> <td>RQ value 100 lbs.</td> </tr> <tr> <td>Sec.302 Extremely hazardous substances</td> <td>no</td> </tr> <tr> <td>CERCLA Hazardous substances</td> <td>no</td> </tr> <tr> <td>Sec 313 Toxic Chemicals</td> <td>no</td> </tr> </table> <p>ADVANTAGES</p> <ul style="list-style-type: none"> • Excellent bond strength • Single package, water based formulation for ease of application • High Impact Resistance • Excellent Water Resistance • Will not Effloresce 	Weight per gallon	14.00 lbs.	Color :	White	Solids by Weight	80.0%	Solids by volume	57%	Flammability	N/A (water based)	Application temperature	55° F and rising	Consistency	trowel	Clean up with warm water and soap		Shelf life 1 year		Volatile Organic Content	0.16 lb/gallon	HMIS Rating	H-1,F-0,R-0, PP-A	RCRA Hazardous Substances	none	SARA Title 111 listing:	RQ value 100 lbs.	Sec.302 Extremely hazardous substances	no	CERCLA Hazardous substances	no	Sec 313 Toxic Chemicals	no
Weight per gallon	14.00 lbs.																																
Color :	White																																
Solids by Weight	80.0%																																
Solids by volume	57%																																
Flammability	N/A (water based)																																
Application temperature	55° F and rising																																
Consistency	trowel																																
Clean up with warm water and soap																																	
Shelf life 1 year																																	
Volatile Organic Content	0.16 lb/gallon																																
HMIS Rating	H-1,F-0,R-0, PP-A																																
RCRA Hazardous Substances	none																																
SARA Title 111 listing:	RQ value 100 lbs.																																
Sec.302 Extremely hazardous substances	no																																
CERCLA Hazardous substances	no																																
Sec 313 Toxic Chemicals	no																																