

SOLAR COATING SYSTEMS



SCS RUST INHIBITOR

SCS Rust Inhibitor is a water based rust inhibitor applied directly over all lightly rusted areas on metal roofs after removal of loose coatings, flaky rust. It has excellent adhesion to galvanized steel and aluminum, and corrosion resistance over carbon steel.

FEATURES:

- **Rohm & Haas - Acrylic Technology.**
- **Corrosion Resistant – Resists flash, rust, and corrosion.**
- **Adhesion - Excellent adhesion to metal.**
- **Easy Application - Single component, spraying will give the best uniformity. It can also be brushed or rolled.**
- **Quick Surface Dry - Material will be dry to touch in approximately 30 minutes, and can be recoated in one hour.**
- **Environmentally Friendly - Water based; Asbestos, lead, and mercury free.**

TYPICAL PHYSICAL PROPERTIES: at 75°F

- | | |
|---------------------------|----------------------------|
| • Color | Red |
| • Solids by Weight | 50 ± 2% |
| • Solids by Volume | 40 ± 2% |
| • Weight | 10 lb./Gal. |
| • Application Rate | 1/2 gal per square. |

LIMITATIONS AND PRECAUTIONS:

Do not apply when ambient temperature is below 50°F. Cold temperatures and high humidity will retard drying.

Store in tightly closed containers and protect from freezing.

Surface must be clean, dry, and free of rust and loose dirt.

Material should be coated with a suitable topcoat.

Disclaimer: Our data is based on information from laboratory tests which are believed to be accurate but all recommendations are made without warranty, since the conditions of use are beyond Solar Coating Systems control. We do not assume liability or responsibility of the product relative to coverage, performance, or injury resulting from its use. Liability, if any, is limited to replacement of product.